

Before Starting Work.

WORK AREA Before Starting Work

there is a danger of explosion. It will ignite Do not use this wallpaper stripper where

- **'**Z fumes from petrol, or gas cylinder.
- plate would scald your face or hands. overhead work - the drips form the steam Do not use this equipment on ceilings or for
- and that no-one is near to you or could Make sure that the area is clear and safe 3
- Well Clear. distract you. Keep children and animals
- Keep your work area clean; wet wallpaper **'**G orners to keep away. Put up warning signs. Protect other people from the steam. Warn ·•
- Move or protect furniture, hot water .9 is very suppery.
- carpets, furnishings and floors. dripping from the steam plate will damage
- Do not stand the boiler unit on decorative
- place it on a heat resistant drip tray. drips of hot water may cause damage, floors or other finish surfaces, the heat or
- ventilation and remove excessive moisture Open doors or windows to improve

- equipment (ppe) are the minimum that The tollowing items of personal protective 1 **SROTAR390**
- environments may require a higher level of should be worn wherever you use this equipment. Particular jobs or
- protection.
- You should wear heavy-duty waterproot .s

ອງປະຊຸ

MALLPAPER STRIPPER

SHC HIRE CENTRES

- bnuot si pnidtyns tl hose and plate. Check your equipment, cables, plugs steam
- damaged, do not use the wallpaper stripper:

uthoritatively interpret the law

contact the hire company.

2450 Regents Court The Crescent Birmingham Business Park Solihull B37 7YE

www.use.org.uk vensue. เมฆเติมชุย.org.uk :lism3 .euoydəjə

have the force of law and only the courts can a

0910 Wallpaper stripper -110/230v

It is important to read all of this leaflet

BEFORE you use the Wallpaper Stripper

be working safely.

or washable paper.

in a careful and controlled way.

2.

3

4.

5.

6.

7.

9

alcohol

care.

Plan your work and think ahead to make sure you will always

Electricity is dangerous and must always be used with great

Electricity and water make a hazardous combination. Keep

some straightforward work before starting on the main task.

waterproof gloves; Rcd if using a 230 volt (mains) supply.

electrical parts away from rain and water.

Steam will scaled or burn instantly; take great care.

Wallpaper Stripper

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

This wallpaper stripper is designed to remove all types of wallpaper, including emulsioned

The action of this wallpaper stripper can cause injury or damage if the equipment is no used

If you have not used a wallpaper stripper before, familiarise yourself with the equipment on

You should have at least the following items of personal protective equipment: Heavy duty

This equipment must not be used by minors, or by anyone under the influence of drugs or

10. This wallpaper stripper is designed for operation by an able bodied adult. Anyone with either

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting mate is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived

.,

·9

1

.S.

.vinpany.

are tight.

to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

temporary or permanent disability must seek expert advice before using it.

you must know how to stop it.

nujeze Joni yands are dry.

protective glove or cloth.

or a blue industrial plug.

- perore you switch the wailpaper stripper on, Check on how the on/off switch operates.

Do not touch electrical switches or plugs

sliowing pressure to release slowly. Use a

equipment is operating and hot. Shut off

Do not remove the filler cap while the

unless specifically recommended by the hire

water only. Additives should not be used

Fill the tank up to the level mark with clean

Before starting, ensure all hose connections

pami buid and arends ismoot a territe aven

designed to run directly from 230v mains will

yourselt when moving it about it may be heavier than you think. Equipment

has been supplied, rake care not to injure

mains 230v supply. If a portable transformer

to power the equipment from a normal

provided a portable transformer if you need

plug fitted is designed to run off a special have

Equipment with a cylindrical yellow industria

matches your supply. Do not try to force

Check that the plug on your equipment

connections or improvise them.

nemqiupa

and allow to cool then remove cap ca





Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

.Dellin

31

company. If the hire company have not given any special instructions given by the hire

2. If you need to use an extension cable, follow

230volt socket. Do not use any

transformer directly into the

110 VOLT HEATERS (YELLOW PLUG)

nstructions below for your equipme

1. If you are using a portable

transtormer,

it will be 100v or 230v.

ELECTRICAL SAFETY

sockets or switches.

use this water again.

away nom you.

TEAM PLATE

seides noisneixe vues.

6nid

pin plug fitted or a blue industrial plug. Read the

230v equipment will have either a normal square

pulg lisitizubni wolley a svaf lliw tnemginpe v0 t t

(our equipment will only operate on one voltage:

DO NOT USE THE STERIM PLATE REAL ELECTRICAL

from the steam plate into it regularly. Do not

fill with water from the steam. Keep a bucket or container handy and empty the water

During use the steam concentrator plate will

sately put the steam plate down when not in

Use a heat resistant drip tray where you can

from the steam holes. Keep the steam plate

concentrator plate will splutter hot water

mears

As the water heats up the

44 (0) 121 380 4600 44 (0) 121 333 4109

e.ora.uk w.hae.org.uk

əuı

Email

For more information on

from HAE by Skipton Hire Centre (SHC) Limited. Document expires on 26/

Using the Wallpaper Stripper

Each section of wallpaper treated will be very hot. Take care while handling it.

Switch off and remove the plug then allow the equipment to cool down completely

Always place the boiler unit on a heat resistant drip tray and not on a decorative surface. Make sure the steam plate is placed on a heat resistant drip tray when not

The part that stays hot longest is the filler cap. Allow it to cool then remove it

carefully with a protective glove or cloth. Remove it in stages, allowing any

If you think the cable may be cut or damaged in any way, switch off and unplug

at the mains before inspecting it. If the cable attached to the wallpaper stripper is

damaged, stop using the equipment. Contact the hire company. If an extension

Switch off and remove the plug from the socket then allow the equipment to cool

10. Switch off and remove the plug then allow the equipment to cool down completely

11. If your equipment does not work properly do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for future reference

12. You may want to read this leaflet again. Please keep it until you finish work.

Keep the cable clear of any sharp edges in your work area.

Take care not to accidentally pull the plug from the socket.

cable has been damaged, do not use it again.

HSE

1.

2

3.

5.

6.

7.

8.

9

Wear your gloves

before refilling.

pressure to release slowly.

down before leaving unattended.

before emptying.

hire company.

in use

health and safety in construction go to

www.hse.gov.uk/construction/

Copyright Hire Association Europe April 2000

are dry and safe 1601 p. Make sure

Association Europ

Birmingham Business Park Solihull B37 7YE

2450 Regents Court The Crescent

catch tire.

<u>ຮບດາວອບບດວ ອເດຂວ ບດເຮບອາxອ</u>

suλ will overheat and could b.

run over it. Unroll it fully or it be trapped, and places where vehicles might edges, doorways or windows where it might

4. Lay it out carefully avoiding liquids,

rue .ca. than 50 metres (160 feet). Plug it directly into

any special instructions, you should only use a suitably rated heavy duty one, not longer company. If the hire company have not given

special instructions given by the hire 3. If you need an extension cable, follow any

- according to the instructions supplied with it. vorking each time you use it. Reset the rod
- 2. Use the "TEST" button to check that the rcd is damaged.

cable or equipment get D:RF0

against electric shock if the will help to protect you equipment into the rcd. This

directly in to the 230 volt socket. Plug your 1. Use a residual current device ("rcd") plugged

(золяве рій ор веле рела) **230 VOLT HEATERS**

connections are dry and safe. 4. Make sure that any extension cable

will overheat and could catch fire. er it. Unroll it fully or it no nu thomas might run ov where it might be trapped, and places where liquids, sharp edges, doorways or windows 3. Lay the extension cable out carefully avoiding

between the transformer and the equipment. You must only use an extension cable cable, not longer than 50 metres (160 feet) any special instructions, you should only use a suitably rated heavy duty 110v extension