



Roughcast Applicator

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet BEFORE using the Roughcast Applicator



1. Cement mixes are harmful to eyes, lungs and skin. Follow any instructions given by the manufacturers of these cement products.
2. This roughcast applicator is designed for the application of a Tyrolean type cement finish to external and internal walls. It will also apply plaster and proprietary paint mixes as a decorative finish.
3. The action of this equipment can cause injury or damage if the equipment is not used in a careful and controlled way.
4. If you have not used a roughcast applicator before, familiarise yourself with how the equipment works before you start on the main task.
5. Plan your work and think ahead to make sure you will always be working safely.
6. You must have at least the following items of personal protective equipment: goggles: EN166 or BS2092; dust mask - a minimum of EN149 ffp2(s) protection; overalls with long sleeves and full trousers; gloves.
7. This equipment must not be used by minors, or by anyone under the influence of drugs or alcohol.
8. This roughcast applicator is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it

Please store this leaflet safely. It may be required for further information



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

©Copyright Hire Association Europe April 2011

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE



- ### Before Starting Work...
1. Do not try to work off ladders, it is unsafe and impractical.
 2. You should carefully mask off window frames, doorframes and other areas where you do not want the cement mix to cover.
 3. Practice on a hidden surface until you can confidently use the machine to get the result you want.
 4. Use both hands to operate the applicator.
 5. If some of the tines are broken or if the inside of the applicator is 'caked' in hardened cement mix, do not use it - contact the hire company.
 6. Make sure you understand how the equipment works, before you mix the first application.
 7. Do not mix too much in one go, the mix may go off before you have used it.
 8. When you have finished work, make sure the applicator is washed clean before the cement mix hardens.
 9. You must clean the applicator as soon as you have finished work before the mix goes hard.
 10. Return the equipment to the hire shop in a clean condition.
 11. If your equipment does not work properly do not attempt to repair it. Contact the hire company.
 12. If you need to work at height you must have a sturdy, safe platform that gives access to large areas of easily so the area must be clear.
 13. Wear your protective equipment including dust mask and goggles.
 14. You need to get to large areas of the surface to be covered quickly and easily so the area must be clear.
 15. If you need to work at height you must have a sturdy, safe platform that gives access to large areas of easily so the area must be clear.



- ### CEMENT MIXES AND CONTACT DERMATITIS
1. Wet cement mix is a substance that can cause contact dermatitis.
 2. Contact dermatitis is a rash that may occur when the skin reacts to certain substances. The rash can vary but it is usually itchy and causes flaky skin. The rash occurs only where the substance was in contact with the skin.
 3. Wash cement or plaster mixes off your skin immediately. Thoroughly rinse out your eyes and seek medical advice if you get any type of cement mix in them.
 4. Mild dermatitis will heal providing there is no further contact. If the rash persists seek medical advice.
- ### WORK AREA
1. Make sure that the area is clear and safe and that no-one is near to you or could distract you.
 2. Protect other people from the spray. Warn others to keep away, put barriers around your work area.
 3. You need easy access to any part of the surface to be covered, so make sure that you have a safe and secure platform if you plan to work over shoulder height.
- ### ROUGHCAST APPLICATOR
1. Check your equipment. If anything is found damaged, do not use the roughcast applicator - contact the hire company.
 2. The following items of personal protective equipment (ppe) are the minimum that should be worn whenever you use this equipment. Particular jobs or environments may require a higher level of protection.
 3. You must wear goggles (EN166 or BS2092) when you are working with this equipment.
 4. You should wear gloves, long sleeves and full trousers to prevent the mixes coming into contact with your bare skin.
 5. Anybody who is working near to you will also need to wear appropriate personal protective equipment.
- ### OPERATORS
1. Rotate the tines by cranking the handle, check that they flick out after being held by the stop.
 2. If some of the tines are broken or if the inside of the applicator is 'caked' in hardened cement mix, do not use it - contact the hire company.
 3. Make sure you understand how the equipment works, before you mix the first application.
 4. Do not mix too much in one go, the mix may go off before you have used it.
 5. When you have finished work, make sure the applicator is washed clean before the cement mix hardens.
 6. You must clean the applicator as soon as you have finished work before the mix goes hard.
 7. Return the equipment to the hire shop in a clean condition.
 8. If your equipment does not work properly do not attempt to repair it. Contact the hire company.
 9. If you need to work at height you must have a sturdy, safe platform that gives access to large areas of easily so the area must be clear.
 10. Wear your protective equipment including dust mask and goggles.
 11. You need to get to large areas of the surface to be covered quickly and easily so the area must be clear.
 12. If you need to work at height you must have a sturdy, safe platform that gives access to large areas of easily so the area must be clear.