



Using the Garden Vacuum/Blower

- Protective equipment must be worn including goggles, dust mask, ear defenders and gloves
- Check that there is no waste material in the machine before the engine is started.
- Never out hands over the vacuum nozzle or the blower outlet while the machine is in operation
- Never point the machine at anyone, not even at a distance.
- If it is necessary to clear a blockage, make an adjustment, or empty the collection bag, the machine must be stopped and the engine and impeller fan allowed to come to a complete stop. For extra safety remove the spark plug lead, this will prevent the engine starting up unexpectedly.
- If any parts or tubes need to be removed to clear the blockage, note/remember how and where they
- All the tubes and parts must be replaced before reconnecting the spark plug lead and starting the
- The engine must be stopped if anyone approaches whilst the operator is working.
- The engine must be stopped before leaving the machine unattended

Please keep this leaflet safely as it may be required for future reference







The Crescent









44 (0) 121 333 4109

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

Please keep this leaflet until the work hat been finished. It may also be required for

- The operator is responsible for the safety and security of the equipment; it should be stored securely especially overnight.

GENERAL

company.

- The vacuum collection bag is not needed when using the machine as a blower. r broperly.
- it into piles, put it in containers and dispose of mont swas and wold blow blow ord else's; else's and on to someone else's; if in containers and it in a senietron or it it in a
- Do not point at, or touch anyone with the

BLOWER

- nacinie is running. Do not attempt to empty the bag while the
- the bag is fully closed before and wait for it to stop completely, and then said wait for it to stop completely, and then accidental espark blug lead to prevent accidental estart. Empty the bag completely and shake it vigorously to remove dust which would otherwise reduce his suction afficiency. Ensure the bag is fully closed before to empty the collection pag, stop the en
- Do not attempt to vacuum up liquids or wet materials, the water will clog up the impeller and damage the machine.

MUUDAN

The cord should be guided back into place so that it recoils correctly. The statter handle should be pulled slowly until the statter has engaged with the engine, then it should be pulled quickly and strongly, it should not be pulled to far, or it may break. The park part of the pulled to a six or it may break. The park part of the pulled to the pulled Make sure that the machine is firmly held so that it will not move when the starter is pulled. If the machine has a fuel primer bulb, depress it 5 to 7 times to draw fuel into the carburettor

rting a machine that is still warm from use, choke control can be set to the 'off'

It starting the machine from cold, adjust the choke control to the coldstart position; if

- Check that the machine and machine controls
- plower mode, this prevents the collection bag it is good practice to start the machine

STARTING THE ENGINE

- changed straight away.

- A funnel should be used when refuelling. Do not spill any fuel on people or the machine.
- ned to prevent dirt falling into the tuel I DE TILLET CAP AND THE AFEA AFOUND IT SHOULD BE
- The oil and petrol MUST be mixed in separate container and NOT in the machine
- stroke oil to 25 measures of petrol (40 ml per itre) instructions on how much oil to use, follow them. Otherwise use 1 measure of the the





Most machines should be set on a firm level surface to start, either on the ground or on a sturdy bench; ensure that there is no debris that could be sucked into and through the machine as it starts up. being inflated until the operator is ready,

company or labels on the machine.

Different machines may have slightly different starting procedures; use these guidelines in conjunction with any instructions from the hire

- Put all fuel caps back on properly, and move the fuel to a safe, cool place. 11. It any tuel is spilled on clothes they must be
- 10. If any fuel is spilled on the ground, wipe it up
- Wipe any fuel off the machine. Dispose of fuel soaked cloth carefully.
- Shake the fuel can to mix the petrol and oil.
- If possible, the machine should be moved away from the work area.
- Stop the engine and let it cool down.







Garden Vacuum/Blower

Safety Instructions

This safety instruction leaflet gives guidance on hand held machines only; most of these will incorporate a harness. Some machines will only operate as a garden vacuum, some are only garden blowers, but most machines can be used as a vacuum or blower.

It is important to read all of this leaflet **BEFORE using the Garden Vacuum/Blower**

1654 Garden blower - 2 stroke petrol

- Petrol is highly flammable. Take care not to cause a fire or exp
- This equipment is designed to blow leaves and other debris from gardens, paths and lawns into corners and other suitable areas, ready to be loaded into bags or containers for disposal, and to vacuum up outdoor areas that are lightly covered with garden debris into the collection bag ready for disposal.
- use, this equipment can cause injury or damage if the machine is not ed carefully and properly;
 - Do not point at, or touch, anyone with the suction nozzle or blower outlet;
 - Removing the vacuum bag on some units may expose the fan/impeller; wait until the engine stops completely;
 - Parts of this equipment get very hot; the operator must take care not to burn
- If the machine is designed to be used with a harness, the harness must be used.
- perator must practice using the controls and operating the equipment before using it, if they have ed it before. This must be done in a safe place until the operator is confident that they cal a it safely.
- The job must be planned to try to forsee any problems that may occur so that they can be safely
- The following is a list of the minimum of Personal Protective Equipment (PPE) that must be worn:
 - Ear muffs or plugs giving protection for levels up to 90dB (A); Impact resistant goggles: EN166 B or BS2092 grade 1;

 - Strong sho
 - Overalls or long sleeves and full trousers;
 - A dust mask may also be required providing a minimum of EN149:2001 ffp2 protection;
 - This machine must not be operated by minors, or by anyone under the influence of drugs or alcohol.is designed for use by an able bodied adult. Anyone with either a temp This garden blower is designed for operation by an able bodied adult. Anyone with either a temp or permanent disability must seek expert advice before using it.













Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability percurates are accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability percurates are accurate and some accurate and statutory institutions. from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.

> 44 (0) 121 333 4109 44 (0) 121 380 4600

BAY 788 Iludilos The Crescent Birmingham Business Park noo sinegen uch



Use a fresh mixture of 2 stroke engine oil with petrol. If the hire company have given special No smoking.

BEFUELLING

The shoulder harness should be put on and adjusted properly before carefully attachings the gattern vacuum. Attach the equipment using only the correct clips and fastenings.

If the hamess attachment points are on the vacuum collection bag it usually means that the hamess only needs to be worn when vacuuming.

If the harmess attachment points are on the machine, the harmess should always be worn machine, the harmess should always be after it has been properly adjusted. This applies to both vacuuming and blowing.

If the machine is designed to be used with a hamess, it is because it is too heavy to be used without it.

SSHNHAH

rstood how to stop it. introls. Before the machine is started it must The operator must understand all of the

Do not use as a vacuum to collect water or other liquids. Do not vacuum anything that is weet. Damp leaves or similar should be blown to a fresh pile before vacuuming, this will

efficiency and overheat the machine. Prolonged vacuuming of fine dusts like sawdust will clog up the collection bag and diminish suction. This will reduce the

ral vacuum, or to pick up litter like cans The equipment should not be used as a Check the engine, collection bag, hamess and all equipment. Anything found to be dismaged should not be used. Contact the

GARDEN BLOWER/VACUUM







In case of an accident it is advisable to work within visual or hearing range of someone who can offer assistance.

Anybody working nearby will also need to vear personal protective clothing.. suarp morns and insects.

rousers must be worn and long sleeves ect against ejected waste material and unid-up of static electricity. Strong gloves should be worn for protection when handling any waste material, Rubber gloves must not be worn; they may cause a gloves must not be worn; they may cause a

If work is being carried out on a dusty surface an appropriate dust mask must be worn (with a minimum of EN149:2001 flp2 protection).

using the equipment or BS2092 grade 1). Impact resistant goggles must be worn .niow ea isum

This equipment is likely to cause noise leve up to 90 dB(A) – appropriate ear muffs plugs giving joaciton for this levenum and provection for this levenum must be aworm mondered to teve

environments may require a migner The following items of personal protective equipment that should bluomarths. Particular the machine. Particular and protective and protective

SHOIAHAYO

before starting the machine, removing hard objects like glass, wire or cans which may injure someone if blown or would damage the machine or collection bag if sucked in. Line work area should be visually che

put warning signs or barriers around the work Other people should be protected from noise and injury. Keep others, especially children and animals well away, it may be necessary to

could cause a distraction.

To reduce the risk of serious or fatal injury from breathing toxic exhaust furnes, the machine should never be used indoors. There must be proper ventiliation when the equipment is being used in confined areas. The area to be worked in should be clear and safe and there should be no-one nearby who could cause a distraction.

umes from petrol, or gas cylinders. to use this equipment near to petrol or storage areas or places where there may n explosive atmosphere. It will ignite a from petrol or to a coulinder.

MORK AREA